



## BFOSC-D48 Domed Fiber Optic Splice Closure Spec Sheet

### 1. Product Information:

The closure is designed with a split end plate for mid access cable applications and includes an integrated slack storage basket, hinged splice tray and an easy to install no special tool sealing system. Constructed with stainless steel hardware, UV stabilized Xenoy (hardened plastic), pass a 20 ft. water immersion test and meet or exceed 150lb. pull out for cables. Each case can be mounted in a variety of ways: cabinet, aerial, wall, above ground, aerial tap mount bracket and pedestal.

### 2. Image:



### 3. Product Specifications

Item	BFOSC-D48
Dimension (mm)	485(440)x165x110
Weight (Kg)	2.65
Diameter of Cable(mm)	15.96mm
No. of Cable Inlet/Outlet	Four
Number of Fibers per Tray	(12 single core)
Max. Number of Trays	4
Max. Number of Fibers	48 (single core)
Sealing of Shells	DRY SEALS (RE-USABLE)

### 4. Kit Contents

Item	Type	Quantity
Fiber Optic Splice Sleeve		48
Self-adhesive cincture	Narrow	1 ROLL
Aerial-Hanger		1 PC
All Weather Tape	Wide	1 PC
Compresion Seal Clamp		1 PC