



ARRIS Touchstone® WTM652A/B/G – Home and Small Office Gateway Technical Specification

Specifications

Physical

Operating Temperature °F (°C)	41 to 122 (5 to 50)
Operating Relative Humidity (Min-Max)	5-85% (Non condensing)
Storage Temperature °F (°C)	-40 to 158 (-40 to 70)
Color	Black
Dimensions (H x W x D) in. (cm)	8.6 x 2.1 x 7.1 (21.8 x 5.3 x 18.0) - excluding F-connector
Weight lbs (kg)	No battery included: 1.2 (0.54)
Battery: 8 Hour Back-up Option (Dark Grey Case)	
Backup Capacity	Lithium-ion 2.4 Ah
Battery Dimensions in. (cm)	1.2 x 1.85 x 3.1 (3.0 x 4.7 x 7.9)
Weight lbs (kg)	1.5 (0.66)
Battery Storage Temperature °F (°C)	-4 to 140 (-20 to 60) Note: Storage above 77°F (25°C) will significantly reduce life of the battery and is not recommended.
Telemetry	AC Fail, Battery Low, Battery Missing, Replace Battery
Diagnostic LEDs	Power, DS, US, Online, Link, Telephone 1, Telephone 2, Battery, Eth 1, Eth 2, Eth 3, Eth 4, Secure, Wi-Fi Activity

Interfaces

RF Interface	External 'F' type connector
Data Interfaces (bridged)	4 x 10/100 Base-T Ethernet (RJ-45 connector)
Telephony Interface	2 lines; RJ-14 ("Line 1/2"), RJ-11 ("Line 2")
Input Voltage (nominal)	100-240 VAC 50/60 Hz

Telephony

Supervisory Voltage	48 VDC nominal
Maximum Loop Length to CPE	1000 ft (457M) of 26 AWG (0.4 mm) wire
Ringing Load Capacity	10 REN total; 5 per line
Provisionable High Loop Current Mode	Yes (40mA constant current source, NA templates ONLY)
Telcordia™ GR 1089 (Lightning and Power Surge) Tested	Yes
Programmable Interface for Worldwide Applications	Yes (supports multiple country templates)

RF Downstream

Frequency Range (MHz)	108-1002
Carrier Bandwidth (MHz)	6 (DOCSIS models), 8 (EuroDOCSIS models)
Modulation (QAM)	64 or 256
Data Rate (Mbps Max.)	up to 51
RF Input Sensitivity Level (dBmV)	-15 to +15
Total Input Power (40-1000MHz, dBmV Max.)	33

Continue to next page.

ARRIS Technical Specification

Specifications Continued

RF Upstream

Frequency Range (MHz)	5 to 42 (DOCSIS), 5 to 65 (EuroDOCSIS)
Modulation	QPSK, 8 QAM, 16 QAM, 32 QAM, 64 QAM & 128 QAM (S-CDMA only)
Data Rate (Mbps Max.)	up to 30.72
RF Output Level (dBmV)	ATDMA: +8 to 54 dBmV (32 QAM, 64 QAM) +8 to 55 dBmV (8 QAM, 16 QAM) +8 to 58 dBmV (QPSK) S-CDMA: +8 to +53 dBmV (all modulations)
Automatic Level Adjust	Yes
Frequency Stability (kHz)	±5
Output Impedance (Ohms)	75

Wireless

Transmit Power Output (EIRP)	19dBm +1/-1.5 dB 802.11b; 16dBm +1/-1.5 802.11g
Receive Levels	>-90dBm 802.11b 11mbps; >-74dBm 802.11g 54mbps

Standards

Codec: G.711, 64 kbps, μ and A-law encoded speech	UL [®] 60950, FCC Part 15 Class B, CE
Enhanced codec firmware support (G.726, G.828, G.729E)	RoHS, WEEE
T.38 Fax Relay	IEEE Std. 802.11b, 1999 Edition
DOCSIS 2.0	IEEE Std. 802.11g, 2002 Edition
PacketCable 1.0 & 1.5 based	Wi-Fi- Alliance, WPA [™] and WPA2 [™] Personal, 64/ 128 bit WEP,
IEEE 802.3, IEEE 802.3ab, IEEE 802.3x, IEEE 802.1p, IEEE 802.1Q	WMM [®] QOS, WMM Power Save
RFC3261 SIP: Session Initiation Protocol	

Battery back-up times are typical and can be influenced by the age of the battery, the charging state, storage conditions and operating temperature as well as factors such as data activity and length of active telephone calls. The capabilities, system requirements and/or compatibility with third-party products described herein are subject to change without notice. Actual operating range may vary according to environmental conditions at the time of use.

Ordering Information

Part Number	Description
DOCSIS 2.0 Models	PacketCable 1.0/1.5 Compliant E-MTA Integrated 100-240 VAC, 50/60 HZ Power supply with 6 foot power cord. Includes Quick Install Guide, Ethernet Cable, and CD-ROM with users guide.
728994	Touchstone WTM652A/NA - NEMA 1 power plug - no battery backup capability.
780120	Touchstone WTM652A/CE - CEE 7/16 Euro power plug - no battery backup capability.
780122	Touchstone WTM652G/CE-0 - CEE 7/16 Euro power plug - battery capable but no battery included.
780123	Touchstone WTM652G/CE-8 - CEE 7/16 Euro power plug - 2 cell, Li-Ion Battery Pack for up to 8 hours of battery back-up.
728995	Touchstone WTM652G/NA-0 - NEMA 1 power plug - battery capable but no battery included.
728996	Touchstone WTM652G/NA-8 - 2 cell, Li-Ion Battery Pack for up to 8 hours of battery back-up.
Euro-DOCSIS 2.0 Models	Euro-PacketCable 1.0/1.5 Compliant E-MTA, Dual Mode Scanning, Integrated 220/240 VAC, 50 HZ Power supply, with 6 foot power cord. Includes Quick Install Guide, Ethernet Cable, and CD-ROM with users guide
780121	Touchstone WTM652B/DM - CEE 7/16 Euro power plug - No battery capability.
Accessories	
721944	2-Cell, 2.4 Ah, Li-Ion Battery Pack for WTM652G (battery models)
718005	4-Cell, 4.4 Ah, Li-Ion Battery Pack for WTM652G (Battery models)
721198	North American NEMA 1-15 plug Power Cord, 6 foot
721197	European CEE 7/16 plug Power Cord, 6 foot

Specifications are subject to change without notice.

The capabilities, system requirements and/or compatibility with third-party products described herein are subject to change without notice. ARRIS, the ARRIS logo, Auspice[®], C3[™], C4[®], C4c[™], Cadant[®], C-COR[®], CHP Max[®], ConvergeMedia[™], Cornerstone[®], CXM[™], D5[™], Digicon[®], Flex Max[®], Keystone[™], MONARCH[®], n5[™], nABLE[™], NSM[™], nVision[®], OpsLogic[®], OpsLogic Service Visibility Portal[™], PLEXIS[®], PowerSense[™], Regal[®], ServAssure[™], Service Visibility Portal[™], TeleWire Supply[®], TLX[®], Touchstone[®], VoiceAssure[™], VSM[™], and WorkAssure[™] are all trademarks of ARRIS Group, Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and the names of their products. ARRIS disclaims proprietary interest in the marks and names of others. © Copyright 2009 ARRIS Group, Inc. All rights reserved. Reproduction in any manner whatsoever without the express written permission of ARRIS Group, Inc. is strictly forbidden. For more information, contact ARRIS.



www.arrisi.com